



Domingo French 831 -
Villa Martelli -
Buenos Aires – Argentina
TE: 011 4709 6650
Ventas@wiretechsa.com.
ar
www.wiretechsa.com.ar

Televisión Digital

DVB-C

VR-2210 Digital Cable / MMDS Television Receiver

El VR-2210 presenta una alta prestación frente a la relación costo-eficiencia del Receptor Digital. Se dispone de versiones que operan con CAS Irdeto, Conax o CTI Communicate, permitiendo la recepción de señales libres tanto para señales de Cable como de MMDS.

Mediante el display se puede realizar un seguimiento de las funciones del VR-2210.



Características

1. Powerful single chip NEC EMM2LL
2. Fully DVB-C / MPEG-2 compliant
3. Irdeto / Conax / others CAS support
4. Multi QAM demodulation selection: QAM16, QAM32, QAM64, QAM128, and QAM256
5. Teletext / Data broadcast support
6. Up to 1000 channels memory space
7. EPG (Electronic Program Guide)
8. Friendly user interface, multi-language OSD
9. NIT automatic search program
10. Favorite channel setting
11. Parent Lock
12. Aspect ratio 4:3 and 16:9
13. Program parameters memorization when power-off
14. PAL / NTSC auto-conversion
15. Over-the-cable (OTC) and RS232 software upgrade
16. CVBS output
17. S/PDIF digital audio output
18. S-VIDEO output
19. RF modulator output (Optional)
20. 18V/250mA DC output to down converter

Especificaciones

Tuner & Channel

Input Frequency: 50~862MHz
Input Level: -25~+20dBmV
Input Impedance: 75Ω
Demodulation: QAM 16, 32, 64, 128, 256
Symbol Rate: 3.0~7.0MS/s

Audio / Video Decoding

Audio Decoding: MPEG-1 & MPEG-2 layer I & II
Audio Mode: Single/Dual Mono / Stereo
Aspect Ratio: 4:3, 16:9
Video Format: PAL / NTSC

System Resources

Flash Memory: 2Mbyte
SDRAM: 8Mbyte

Front Panel

LED: 2 LEDs

Buttons: 6 keys

Display: 4 digits & 8 segments

Smart Card: 1 slot, ISO 7816

Rear Panel

RF Input: F – Type, Loop through

RCA Output: 2 Video, 4 Audio (2 Lefts, 2 Rights)

Digital Audio: 1 S/PDIF output

S-VIDEO: 1 S-VIDEO output

Data Port: 1 RS232, 9 PIN D-Sub Type

RF modulator Output: IEC169-2 Male&Female (Optional)

Physical Specifications

Input Voltage: 90-250VAC, 50/60Hz

Power Consumption: Max 10W

Size (WxHxD): 305 x 42 x 245 mm

Net Weight: 1.8 Kg

Operating Temp: 0 – 45 °C

