Modelo: NCMISPXX	ESPECIFICACIONES TECNICAS	Wire Tech
Fecha: 2013		
Hojas 1 de 1		
Asunto	SPLITTER DOMICILIARIO	

1 GHz INDOOR SPLITTERS

NCM SUPPLIES

MODEL: NCM-ISPXX

Features

- Nickel plated zinc housing
- 1 GHz bandwidth
- Low loss characteristics
- Blocking capacitors installed
- Integrate mounting tabs and grounding block

Specifications

NCM-ISP03 INSERTION LOSS (dB) MAX	FREQUENCY (MHz)							
	10	150	300	450	550	750	870	1000
ISP-02	3.5	3.5	3.5	3.7	3.7	3.7	3.8	3.9
ISP-03	3.5/7.1	3.5/7.0	3.5/7.0	3.7/7.2	3.7/7.3	3.7/7.5	3.8/7.6	3.9/7.8
ISP-04	7.1	7.1	7.1	7.2	7.3	7.5	7.6	7.8
RETURN LOSS (dB) MIN								
ISP-02	23	23	21	20	19	16	16	15
ISP-03	23	23	20	20	19	17	18	16
ISP-04	23	23	20	20	19	17	18	16
ISOLATION (dB) MIN								
ISP-02	32	33	30	30	30	30	30	30
ISP-03	27	29	29	27	28	25	25	25
ISP-04	27	29	29	27	28	25	25	25
EMI SHIELDING (dB) MIN								
ALL MODELS MIN	120	120	120	120	120	120	120	120