

CONECTOR F11 COMPRESION



EX[®] Universal Compression Connectors EX11N716MP Movable Push-up Pin Connector

Installers are faced with the problem of identifying old unmarked 60% through Quad Shield Series 11 cable, and having to guess which connector is the best match. This results in unnecessary service calls due to the use of the wrong connector/cable match.

The unique patented design of the EX[®] body achieves true universality on 60% through Quad Shield, PE, and PVC jacket.



EX11N716MP

Specifications

Bandwidth	0 MHz to 3 GHz
Impedance	75 Ohms (nominal)
Return Loss	Minimum -35 dB to 1 GHz Minimum -25 dB to 3 GHz
Insertion Loss	< .10 dB to 1 GHz
Operating Voltage	90 V (at 60 Hz continuous AC)
Operating Temperature	-40° F to + 140° F (-40° C to 60° C)
Cable Retention (Trishield)	75 lbs (34.02 kg) minimum

MODELO

EX11N716MP

CODIGO WT

4091114

Casa Central

Domingo French 831, B1603BNI, Villa Martelli, BS AS, Argentina
Tel:(54) 011-4709-6650
ventas@wiretechsa.com.ar

Sucursal Córdoba

Diaguítas 3138, Córdoba, CP 5008, Argentina
Te:(54) 0351 476-1313 – 0908
sucursalcordoba@wiretechsa.com.ar