

Plataforma Digital DHP400 Modulo DX902

DESING



DESCRIPCION

Modulo Entrada 2 Sintonizadores DVB-S2
Para Plataforma DHP400

MODELO

DX902

CODIGO WT

4223416

Casa Central

Domingo French 831, B1603BNI, Villa Martelli, BS AS, Argentina
Tel:(54) 011-4709-6650
ventas@wiretechsa.com.ar

Sucursal Córdoba

Diaguítas 3138, Córdoba, CP 5008, Argentina
Te:(54) 0351 476-1313 – 0908
sucursalcordoba@wiretechsa.com.ar

1 - APLICACIÓN

Module Specifications:

Stream in: 2 Tuner input, F Type

DVB-CI: 2 independent common interface slots

Standard: DX902: DVB-S/S2; DX912: DVB-C

Tuner Section	DVB-S	Input Frequency: 950-2150MHz Symbol Rate: QPSK 1~45Mbauds Signal Strength: -65~-25dBm FEC Demodulation: 1/2, 2/3, 3/4, 5/6, 7/8
	DVB-S2	Input Frequency: 950-2150MHz Symbol rate: QPSK/8PSK 1~45Mpsps 16APSK 1~45 Mpsps 32APSK1~32 Mpsps FEC Demodulation: 1/2, 2/3, 3/4,5/6,7/8, 4/5,5/6,8/9, 9/10
	DVB-C	Standard: J.83A(DVB-C), J.83B, J.83C Input Frequency: 30-960MHz Constellation: 16/32/64/128/256 QAM

Support Diseqc function (For DX902)

Multiplexing:

Maximum PID Remapping: 256 input

Function: PID remapping (automatically or manually), Accurate PCR adjusting, generate PSI/ SI table automatically

Descrambling:

CAM/CI Quantity: 2

BISS Mode: Mode 1, Mode E; up to 120Mbps (Optional as required)

2 – Características Físicas

2 Tuner Descrambling Module



DX902/DX912