

RACK DE DISTRIBUCION PARA 576 FO



Optical cable inlet unit

72-core integrated unit for splice and distribution



The dimension of above figure:
2200 x 840 x 300mm

DESCRIPCION

8 Patch Panel de 76 FO C/U + Organizador
576 Acopladores SC/APC + 256 SC/UPC

MODELO

GP82-4

CODIGO WT

4241716

Casa Central

Domingo French 831, B1603BNI, Villa Martelli, BS AS, Argentina
Tel:(54) 011-4709-6650
ventas@wiretechsa.com.ar

Sucursal Córdoba

Diaguítas 3138, Córdoba, CP 5008, Argentina
Te:(54) 0351 476-1313 – 0908
sucursalcordoba@wiretechsa.com.ar

1 – PATCH PANEL



2 - ESPECIFICACIONES

	Dimensions (H*W*D)mm	Panels	Max Capacity (FC)	Max Capacity (SC/LC)		Dimensions (H*W*D)mm	Panels	Capacity
GPX82-2	2600*840*300	12	864	1728	GPX82-1-2	2600*900*300	8	576
	2200*840*300	8	576	1152		2200*900*300	6	432
	2000*840*300	7	504	1008		2000*900*300	4	288
GPX82-4	2600*840*300	12	864	1728		2600*600*300	4	288
	2200*840*300	8	576	1152		2200*300*300	3	216
	2000*840*300	7	504	1008		2000*600*300	2	144
	Description	Dimensions (H*W*D)mm		Capacity		Remark		
GPX 82-6B	Fiber Storage Frame	2200*480*700				Disc-shape splice trays and 6-position adapter holders are adopted.		
	Integrated Splice Frame	2200*720*700		12 FO /tray, 144trays/frame				
	Basic Distribution Frame	2200*900*700		72 FO /unit, 864FO(12units)/frame				
	Expansion Distribution Frame	2200*900*700		72 FO /unit, 864FO(12units)/frame				