

CAJA NAP 16 Acopladores SC/APC – PLC 1*8

OPF
-optical fiber latam-



D4: 16F Rubber grommet;
2 single input, one oval input



OPF-CTO-16-LE-A4-D4

DESCRIPCION

NAP 16 SC/APC + PLC 1*8 – 16 Entradas
LEGO

MODELO

OPF-CTO-16-LE-A4-D4

CODIGO WT

4274227

Casa Central

Domingo French 831, B1603BNI, Villa Martelli, BS AS, Argentina
Tel:(54) 011-4709-6650
ventas@wiretechsa.com.ar

Sucursal Córdoba

Diaguitas 3138, Córdoba, CP 5008, Argentina
Te:(54) 0351 476-1313 – 0908
sucursalcordoba@wiretechsa.com.ar

1 - APLICACIÓN

Considerando la situación práctica en la aplicación de campo, OPF-CTO-16-LE es desarrollado por OPFIBRA

Esta caja FTTH se puede utilizar:

- 1- Para empalmes, puede contener más de 72 núcleos.
- 2- Para parchear, puede contener más de 16 piezas de gota cables para 16 abonados.
- 3- Como terminal de acceso de fibra, puede admitir 8/12 piezas de SC adaptadores para 8/12 suscriptores.

OPF-CTO-16-LE también puede admitir varios tipos de cable de fibra, tanto para exteriores como para interiores, cable de caída de 2 * 3 mm, máx. 15 mm situación de emergencia, reemplazando los componentes en el interior, OPF-CTO-16-LE se puede utilizar para 2 aplicaciones.

2 - CARACTERISTICAS

1. FEATURES

- Dis-mountable adaptor panel
- Support midspan termination
- Easy operation and installation
- Rotatable and dis-mountable splice tray for easy splicing
- IP65 sealing.
- Supporting Blockless PLC Splitters or Insertion Module PLC Splitters
- Supporting various application by replacing components inside.

2. APPLICATIONS

- Wall mounting & pole mounting installation
- Suitable for 2*3mm Indoor FTTH Drop Cable, Outdoor 2*5mm Figure 8 FTTH Drop Cable, 2*3mm, 2*5mm, &5mm Pre-terminated Drop Cable.



| | |
|------------------|--|
| Input Cable Size | Φ12-Φ15mm |
| Out Cable Size | Drop Cable: 2*3mm, 2*5mm Round Cable: Φ3mm to Φ4mm |

| Material | Size | Max Capacity | Empty Weight | Loaded Weight | Color |
|----------|------------|--------------|--------------|---------------|-------|
| | A*B*C (mm) | SC | | | |
| PC + ABS | 272*200*84 | 16 Ports | kg | kg | black |

3 – ESPECIFICACIONES

| Model | OPF-CTO-16-LE-A3-D2 | OPF-CTO-16-LE-A3-D4 | OPF-CTO-16-LE-A4-D2 | OPF-CTO-16-LE-A34-D4 | OPF-CTO-16-LE-A1-D2 | OPF-CTO-16-LE-A1-D4 | OPF-CTO-16-LE-A2-D1 | OPF-CTO-16-LE-A2-D3 |
|----------------------|-------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|--|--|
| Inner Structure | A3: inclined adapter panel | A3: inclined adapter panel | A4: vertical adapter panel | A4: vertical adapter panel | A1: For insertion Splitter | A1: For insertion Splitter | A2: Splice tray | A2: Splice tray |
| Bottom Astructure | D2: rubber clamp | D4: rubber grommet | D2: rubber clamp | D4: rubber grommet | D2: rubber clamp | D: rubber grommet | D1: pre-terminated adapter | D3: pre-terminated adapter |
| Adapter | 16 pcs of SC | 16 pcs of SC | 16 pcs of SC | 16 pcs of SC | 16 pcs of SC | 16 pcs of SC | 8pcs of waterproof SC | 12 pcs of waterproof SC |
| Splitter | 1pc of 1*16 or 2pc of 1*8 | 1pc of 1*16 or 2pc of 1*8 | 1pc of 1*16 or 2pc of 1*8 | 1pc of 1*16 or 3pc of 1*8 | 1pc of 1*16 or 2pc of 1*8 | 1pc of 1*16 or 3pc of 1*8 | 1pc of 1*8 | 1pc of 1*8 |
| Splitter Package | blockless | blockless | blockless | blockless | Insertion | Insertion | blockless | blockless |
| Max. Splice Capacity | 16 fibers | 60 fibers (12 fibers/tray) | 60 fibers (12 fibers/tray) | 60 fibers (12 fibers/tray) | 16 fibers | 16 fibers | 60 fibers (12 fibers/tray) | 60 fibers (12 fibers/tray) |
| Input Ports | 1 oval uncut port and 2 round ports | 1 oval uncut port and 2 round ports | 1 oval uncut port and 2 round ports | 1 oval uncut port and 2 round ports | 1 oval uncut port and 2 round ports | 1 oval uncut port and 2 round ports | 1 oval uncut port and 2 round ports | 1 round ports |
| Output Ports | 16 ports | 16 ports | 16 ports | 16 ports | 16 ports | 16 ports | 8 ports | 12 ports |
| Output Cable Size | Drop cable 2*3mm, 2*5mm | Drop cable 2*3mm, 2*5mm | Drop cable 2*3mm, 2*5mm | Drop cable 2*3mm, 2*5mm | Drop cable 2*3mm, 2*5mm | Drop cable 2*3mm, 2*5mm | Drop cable 2*3mm, 2*5mm, round cable 5mm | Drop cable 2*3mm, 2*5mm, round cable 5mm |
| Dimension (mm) | 272*200*84 | 272*200*84 | 272*200*84 | 272*200*84 | 272*200*84 | 272*200*84 | 272*200*84 | 272*200*84 |

4 – ACSESORIOS

